



# Hochfeste S-Haken, offene Form, kurze Ausführung



Artikelnummer	Tragfähigkeit (kg)	Maß D (mm)	Maß a (mm)	Maß b (mm)	Gewicht (kg)
S10	200	10	80	25	0,1
S13	300	13	100	30	0,2
S16	500	16	130	40	0,5
S18	750	18	160	50	0,7
S20	1000	20	180	55	1
S22	1250	22	200	60	1,3
S26	1500	26	220	65	2
S32	2000	32	260	80	3,6
S36	3000	36	320	95	5,6
S40	4000	40	360	110	7,9
S45	5000	45	400	120	11
S50	6000	50	450	135	15,3

# Hochfeste S-Haken, offene Form, lange Ausführung



Artikelnummer	Tragfähigkeit (kg)	Maß D (mm)	Maß a (mm)	Maß b (mm)	Gewicht (kg)
S08L	100	8	115	28	0,1
S10L	150	10	115	28	0,1
S12L	250	12	153	38	0,2
S14L	350	14	191	50	0,4
S16L	500	16	229	63	0,7
S20L	750	20	267	76	1,2
S22L	1000	22	305	88	1,9
S26L	1300	26	331	101	2,7
S28L	1500	28	381	114	3,9
S32L	2000	32	407	127	5,3
S36L	2400	36	432	139	7
S38L	2800	38	460	150	8,8
S40L	3200	40	500	160	10