



Hochfeste Schkel / S - Haken



Artikel Nr.	Tragfhigkeit in t
FS.SGH033	0,33
FS.SGH05	0,5
FS.SGH075	0,75
FS.SGH1	1,0
FS.SG15	1,5
FS.SGH2	2,0
FS.SGH325	3,25
FS.SGH475	4,75
FS.SGH65	6,5
FS.SGH85	8,5
FS.SGH95	9,5
FS.SGH12	12,0
FS.SGH135	13,5
FS.SGH17	17,0
FS.SGH25	25,0
FS.SGH35	35,0
FS.SGH55	55,0

Mae Schkel geschweit			
A	B	C	D
9,5	5,0	21,0	6,3
11,9	6,4	24,6	8,0
13,5	7,9	27,2	9,5
16,8	9,6	32,5	11,0
19,0	11,2	37,6	12,7
20,6	12,7	40,7	16,0
27,0	16,0	50,0	19,0
31,8	19,0	59,5	22,2
36,6	22,0	71,0	25,4
43,0	25,0	80,5	28,5
46,0	28,0	90,0	31,7
51,5	32,0	100,0	35,1
57,0	35,0	111,0	38,0
60,5	38,0	124,0	41,5
73,0	45,0	145,5	50,8
82,5	51,0	169,5	57,1
105,0	65,0	202,0	69,8

Artikel Nr.	Tragfhigkeit in t
FS.SGH05S	0,5
FS.SGH075S	0,75
FS.SGH1S	1,0
FS.SG15S	1,5
FS.SGH2S	2,0
FS.SGH325S	3,25
FS.SGH475S	4,75
FS.SGH65S	6,5
FS.SGH85S	8,5
FS.SGH95S	9,5
FS.SGH12S	12,0
FS.SGH135S	13,5
FS.SGH17S	17,0
FS.SGH25S	25,0
FS.SGH35S	35,0
FS.SGH55S	55,0



Artikel Nr.	Tragfhigkeit in t
gerade Form Augbolzen	
FS.SH033	0,33
FS.SH05	0,5
FS.SH075	0,75
FS.SH1	1,0
FS.SG15	1,5
FS.SH2	2,0
FS.SH325	3,25
FS.SH475	4,75
FS.SH65	6,5
FS.SH85	8,5
FS.SH95	9,5
FS.SH12	12,0
FS.SH135	13,5
FS.SH17	17,0
FS.SH25	25,0
FS.SH35	35,0
FS.SH55	55,0

Mae Schkel gerade			
A	B	C	D
9,5	5,0	21,0	6,3
11,9	6,4	24,6	8,0
13,5	7,9	27,2	9,5
16,8	9,6	32,5	11,0
19,0	11,2	37,6	12,7
20,6	12,7	40,7	16,0
27,0	16,0	50,0	19,0
31,8	19,0	59,5	22,2
36,6	22,0	71,0	25,4
43,0	25,0	80,5	28,5
46,0	28,0	90,0	31,7
51,5	32,0	100,0	35,1
57,0	35,0	111,0	38,0
60,5	38,0	124,0	41,5
73,0	45,0	145,5	50,8
82,5	51,0	169,5	57,1
105,0	65,0	202,0	69,8

Artikel Nr.	Tragfhigkeit in t
gerade Form M/S	
FS.SH05S	0,5
FS.SH075S	0,75
FS.SH1S	1,0
FS.SG15S	1,5
FS.SH2S	2,0
FS.SH325S	3,25
FS.SH475S	4,75
FS.SH65S	6,5
FS.SH85S	8,5
FS.SH95S	9,5
FS.SH12S	12,0
FS.SH135S	13,5
FS.SH17S	17,0
FS.SH25S	25,0
FS.SH35S	35,0
FS.SH55S	55,0



Artikel Nr.	Tragfhigkeit in t
S - Haken offene kurze Form	
S10	0,2
S13	0,3
S16	0,5
S18	0,75
S20	1,0
S22	1,25
S26	1,5
S32	2,0
S36	3,0
S40	4,0
S45	5,0
S50	6,0

Mae S-Haken offen kurze Form mm		
D	a	b
10,0	80,0	25,0
13,0	100,0	30,0
16,0	130,0	40,0
18,0	160,0	50,0
20,0	180,0	55,0
22,0	200,0	60,0
26,0	220,0	65,0
32,0	260,0	80,0
36,0	320,0	95,0
40,0	360,0	110,0
45,0	400,0	120,0
50,0	450,0	135,0

Artikel Nr.	Tragfhigkeit in t
S - Haken offene lange Form	
S10L	0,15
S13L	0,25
S16L	0,35
S18 L	0,50
S20L	0,75
S22L	1,00
S26L	1,30
S32L	1,50
S36L	2,00
S40L	2,40
S45L	2,80
S50L	3,20

Mae S-Haken offen lange Form mm		
D	a	b
10,0	115,0	28,0
12,0	153,0	38,0
14,0	191,0	50,0
16,0	229,0	63,0
20,0	267,0	76,0
22,0	305,0	88,0
26,0	331,0	101,0
28,0	381,0	114,0
32,0	407,0	127,0
36,0	432,0	139,0
38,0	460,0	150,0
40,0	500,0	160,0

Wir sind seit Jahren ein verlsslicher Partner fr Industrie und Handwerk
und freuen uns auf Ihre Anfrage
Tel. : 0203-518660 E-Mail : info@anschlagmittel-imm.de